SI.	SECTION	NAMES OF THE ITEMS	NAMES OF THE BRAND / MANUFACTURER / SUPPLIER		
1	SECTION - A	BRICKS &BUILDING BLOCKS	Aerocon, Siporex, Nucon, NCL,		
2	SECTION - B	NATURAL FLOORING TILES			
3	SECTION - C	WALL & FLOOR TILES	Somany, NaveenCeramics, Kajaria, Nitco, Segno, Sphinx, Orient Bell, AGL, Hindware, Bisazza, Marblex, Amstrong.		
		TILE ADHESIVES	MYK LATICRETE		
4	SECTION - D	PAVING & INTERLOCKING TILES	Super Decorative, Aditya Designer, Maha Bhima, Tricon Pheonix, Eurocon, Ultra, Sphinx		
5	SECTION - E	TIMBER & ROOFING MATERIALS			
6	SECTION - F	MILD, GALVANISED & STAINLESS STEEL	R.K Steels, Sugna TMT Bars, Shyam Steels, Mangal TMT, Manga TMT 999		
7	SECTION - G	FIXTURES FOR DOOR & WINDOWS	oti, Classic, Hardwyn		
8	SECTION-H	WATER PROOFING CHEMICALS & ADMIXTURES	MULTI CHEM, MYK LATRICRETE, WALRUS, Clean Tech Corri Chemicals, ESSAR,		
9	SECTION-I	GLASS	Modi, Saintgobain, Asahi, Binani, HNG		
10	SECTION - J	PAINTS & POLISHES	Asian, Berger, Nerolac, British Paints, JK Paints, Saico Indocem, ESSAR, Sheenlac, Suryacem, PMCC, Neon,Gl FLANKS (Wallz), Walrus – SYNTHETIC PLASTER - NCL Allto MYK LATICRETE, Multichem, GRA Flanks, INDOCEM, Nippon.		
11	SECTION - K	PARTICLE BOARDS	NCL Bison, Ramco-Hilux, Ramco-Hicem, Everest-boar Visakha-board, Rajshri, Innsula, Aerocon, Aerolite, Novops Bhutan-board, Green ply		
12	SECTION - L	PLYWOOD	Kitply, Century Ply, National Ply, BhutanPly, Samrat, Gurjan p AAMODA PLY, NCL, Green ply		
13	SECTION - M	CEILINGS, WALL PARTITIONS & WALL LININGS	Ramco-Hilux, Everest-board, Visakha-board, Rajshri, Innsula Gypsum India, Saintgobain, Armstrong, Daikin, NCL-Seccolor NCL Bison, DORMA, NCL, Aerolite, RONDO		
14	SECTION - N	DOORS	Anand, Raavila, Kutty, Standard, Shubhdwar, ITP, Rajsh NCL-Bison, Elixir, Sintex, Elgi, Oasis, Polywood, Sintex, NC Wintech, Fenesta, LG, Masonite, Everest, Vishaka, Ambiend Aamoda, ALPINE, DORMA, Nagarjuna, NCL Altek & Seccola AHLADA.		
15	SECTION - P	WINDOWS	LG, AHLADA, NCL Altek & Seccolor, NCL-Bison, Elixir, Sintex, Elgi, Oasis, Polywood, NCL-Wintech, Fenesta.		
16	SECTION - Q	STRUCTURAL GLAZING	NCL-Seccolor, NCL-Bison, Elixir, Sintex, Elgi, Oasis, Polywood, Sintex, NCL-Wintech, Fenesta, LG		
17	SECTION - U	EXPANSION JOINT FILLERS	Silseal, Silflex, Armour, Shalitex		
18	SECTION - W	MISCELLANEOUS ITEMS	Sintex for PVC tanks, Centurywells for Galvalume sheets, Elix for PEB structures, smart coat, Alluminium Sections - Hindalco, Nalco, Jindal, Plywood - Kitply, Century Ply, National Ply, Bhuta Ply, Green Ply, JK Cement Itd, RONDO		

Note: 1) All Building Materials conforming to ISI Standards, shall be used in all CIVIL, Water Supply & Sanitary Fittings and Electrical Works.

²⁾ Not only limiting to the Brand / Manufacturer / Supplier for Materials/Products mentioned above, Material / Product conforming to the Specification and Standards of ISI from any Brand / Manufacturer, shall also be allowed in all CIVIL, Water Supply & Sanitary Fitings and Electrical Works too.

SI. No	Item Code	Description of item	Unit	Rate for SoR 2015-16
		3	4	5
1	2	BONDING AGENTS		
			1 Ltr	150
422		Acrylic based Bonding adhesive	1 Kg	450
423	BMT-H.122	Styrene butadiene rubber based bonding agent		070
423	DIVITATION	Two Parts system of Epoxy Bonding adhesive Conforming to ASTM-C 881	1 Kg	870
424	BMT-H.123	ANTI-CORROSIVE AGENTS		350
		A will be be sed Anti-corresive coating	1 Ltr	480
425	BMT-H.124		1 Ltr 1 Kg	750
426	BMT-H.125	Rust converter -rust encapsulating coating of section 2 inc rich High range of reinforcement / steel protector against corrosion zinc rich	1 Ng	
427	BMT-H.126	The state of the s	1 Lit	315
428	BMT-H.127	Anti corrosion CRPPC (Corrosion Resistant) inhibitive admixts		
420	Dist 1-11-12	GROUIS	1 Kg	300
429	BMT-H.128	High Power Polyester Resin Anchor Grout Conforming to ASTM-827	1 Kg	34
430	BMT-H.129	Non-shrink Free flow high strength precision grout comorning to		50.00
430	SIMITALIES	Part 1161983	1 Kg	800
431	BMT-H,130	the Franciscopin injection grout	1 Kg	160
432	BMT-H.131	Three component epoxy grout Conforming to is. As in oz.		
402	and shire!			
		MISCELLANEOUS CHEMICALS	1 Ltr	145
433	BMT-H.132	Mould / Shutter releasing oil	1 Kg	37
434	BMT-H.133	Non oxidizing, heavy duty metallic Floor Hardeners	1 Kg	30
435	BMT-H.134	Non-metallic Floor Hardeners High Strength, Non-shrink Micro Concrete for structural repair product.	1 Kg	36
436	BMT-H.135	High Strength, Non-shrink Micro Concrete for saldcts of Popular (Two Structural graded polymer modified reinstatement concrete / mortar (Two	1 Kg	85
437	BMT-H.136	Structural graded polymer modified reinstatement construction		
	-	Part System) Three Component high performance elastomeric mortar.	1 Kg	950
438	BMT-H.137	Surface treatment crystalline product.	1 Kg	360
439	BMT-H.138	Polyurethane Sealant, 600 ml tube	1 No	730
440	BMT-H.139	Polysulphide Sealant.	1 Kg	450
441	BMT-H.140	Acrylic Latex caulking compound.	1 Kg	335 85
442	BMT-H.141	tilles sement based plugging compound	1 Kg	650
443	BMT-H.142	Fast setting cement based programs Highly Flexible High Range Polyurethane surface coatings	1 Ltr	190
444	BMT-H.143	a IT-Fueur	1 Kg	100
445	BMT-H.144	The Display Light nower Cliffing Composition	1 Kg	120
446	BMT-H.145	to the heat compound	1 Kg	85
447	BMT-H.146	Bitumen solution primer coating.	1 Kg	
448	BMT-H.147		1 Ltr	120
449	BMT-H,148	Air Entraining Agent Conforming to IS: 9103-99		
450	ВМТ-Н.149	Providing Tar Felting roof repair with approved brand Tar Felt duly applying one coat of appropriate grade of bitumen in hot condition @ 0.2 Kg/1 Sqm of roof area, fixing tar felt (Conforming to IS 1322-1972 specification), applying second coat of appropriate grade of hot bitumen at 1.20 Kg / 1 Sqm of roof area and spreading course aggregate (sand) at 0.063 Cum per 1 Sqm of	1 Sqm	260
451	BMT-H.150	roof area finished item. Providing waterproofing treatment by supplying and fixing synthetic membrane felt of 1.50 mm thickness, 2.25 Kg per Sq. Mtr. duly applying one coat of Bituminous Emulsion, first coat of bituminous grade 85/25, fix waterproofing membrane, applying second coat of bitumen grade 90/15 after sealing all the joints and abutments with a Gas torch and applying one coat sealing all the joints and abutments with a Gas torch and applying one coat sealing all the joints and abutments with a Gas torch and applying one coat sealing all the joints and abutments.	1 Sqm	
452	BMT-H.151	of bituminous aluminum paint for heat resistance. Providing and laying of 3mm thick app modified bitumen membrane treatment to the terrace duly [1] removing of existing tar felt. [2] cleaning of the surface from dirt, dust and other contaminations. [3] application of one coat of Bitumen dirt, dust and other contaminations. [3] application of one coat of Bitumen primer [4] providing and laying of 3mm thick APP Modified Bitumen Membrane with 100 mm gyerlap fixing with butane torch.		
453	3 BMT-H.15	anacialized high performance activity polytics		